

## INSTALLING FLOOD SENSORS

### INSTRUCTIONS - INSTALLING A WIRELESS FLOOD DETECTOR

- 1- Unpack the Honeywell flood detector, if purchased, and keep all instruction manuals for later use.
- 2- ALWAYS install all flood detectors per local, national and fire codes. Fox Guard shall not be held liable for product installed incorrectly, or installations that do not meet current code requirements.
- 3- Place flood detectors in laundry rooms, near sinks and hot water heaters. For maximum protection install flood detectors on each level and near potential flood causing devices. See installation manual for detailed instructions.
- 4- Note that the Honeywell Low Temp and Flood detector are 2 independent types of devices but are both monitored through the temperature detector 5821 unit. The flood detector, if selected wires to the temperature sensing wireless unit. See temperature detector instructions for details.
- 5- Mount the flood detector on a clean, dirt free area on the floor near the desired protection area using the supplied double sided tape (GOOD) or an included #6 screw (BETTER)
- 5- Make note on section 8-1 for each temperature sensor that also utilizes a flood detector.



Thank you for your purchase from Fox Guard Security. If you need further instruction for this specific product feel free to visit our support section of [Foxguardsecurity.com](http://Foxguardsecurity.com) or our video library on our growing You Tube channel.

*continued...*

# INSTALL TEMPERATURE SENSORS

## INSTRUCTIONS - INSTALLING A WIRELESS TEMPERATURE DETECTOR

1- Unpack the Honeywell wireless temperature detector and keep all instruction manuals for later use.

2- ALWAYS install all temperature detectors per local, national and fire codes. Fox Guard shall not be held liable for product installed incorrectly, or installations that do not meet current code requirements.

3- Place temperature detectors in laundry rooms, near sinks and hot water heaters. For maximum protection install temperature detectors on each level and near potential flood causing devices, if used in conjunction with the optional flood .

See installation manual for detailed instructions.

4- Note that the Honeywell Low Temp and Flood detector are 2 independent types of devices but are both monitored through the temperature detector 5821 unit. The flood detector, if selected wires to this temperature sensing wireless unit. See flood detector instructions in section 8-2.

5- Mount the device to the wall near the desired protection area using the supplied double sided tape (GOOD) or the included #6 screws (BETTER). Release the mounting base by depressing the tab located under the battery location inside the detector itself.

5- Remove the RFID sticker from the included mounting base and place in the correct box and keep this sheet for programming later. DO NOT mix up these numbers.



Flood?  
From 8-2

Flood Detector 1 \_\_\_\_\_

F

Flood Detector 2 \_\_\_\_\_

F

Flood Detector 3 \_\_\_\_\_

F